

610873-00 MOBILGEAR 630  
MATERIAL SAFETY DATA BULLETIN

-----  
**1. PRODUCT AND COMPANY IDENTIFICATION**  
-----

PRODUCT NAME: MOBILGEAR 630  
SUPPLIER: MOBIL OIL CORP.  
NORTH AMERICA MARKETING AND REFINING  
3225 GALLOW'S RD.  
FAIRFAX, VA 22037  
24 - Hour Emergency (call collect): 609-737-4411  
Product and MSDS Information: 800-662-4525 856-224-4644  
CHEMTREC: 800-424-9300 202-403-7616

-----  
**2. COMPOSITION/INFORMATION ON INGREDIENTS**  
-----

CHEMICAL NAMES AND SYNONYMS: PET. HYDROCARBONS AND ADDITIVES  
INGREDIENTS CONSIDERED HAZARDOUS TO HEALTH:  
This product is not formulated to contain ingredients which have exposure limits established by U.S. agencies. It is not hazardous to health as defined by the European Union Dangerous Substances/Preparations Directives. See Section 15 for a regulatory analysis of the ingredients.  
See Section 15 for European Label Information.  
See Section 8 for exposure limits (if applicable).

-----  
**3. HAZARDS IDENTIFICATION**  
-----

US OSHA HAZARD COMMUNICATION STANDARD: Product assessed in accordance with OSHA 29 CFR 1910.1200 and determined not to be hazardous.  
EFFECTS OF OVEREXPOSURE: No significant effects expected.  
EMERGENCY RESPONSE DATA: Slightly Hazy Amber Liquid. DOT ERG No. - NA

-----  
**4. FIRST AID MEASURES**  
-----

EYE CONTACT: Flush thoroughly with water. If irritation occurs, call a physician.  
SKIN CONTACT: Wash contact areas with soap and water.  
INHALATION: Not expected to be a problem.  
INGESTION: Not expected to be a problem. However, if greater than 1/2 liter (pint) ingested, seek medical attention.

-----  
**5. FIRE-FIGHTING MEASURES**  
-----

EXTINGUISHING MEDIA: Carbon dioxide, foam, dry chemical and water fog  
SPECIAL FIRE FIGHTING PROCEDURES: Water or foam may cause frothing. Use water to keep fire exposed containers cool. Water spray may be used to flush spills away from exposure. Prevent runoff from fire control or dilution from entering streams, sewers, or

drinking water supply.

**SPECIAL PROTECTIVE EQUIPMENT:** For fires in enclosed areas, fire fighters must use self-contained breathing apparatus.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** None. Flash Point C(F): > 204(400) (ASTM D-92). Flammable limits - LEL: NA, UEL: NA.

**NFPA HAZARD ID:** Health: 0, Flammability: 1, Reactivity: 0

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide. Elemental oxides  
Metal oxides.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

**NOTIFICATION PROCEDURES:** Report spills as required to appropriate authorities. U. S. Coast Guard regulations require immediate reporting of spills that could reach any waterway including intermittent dry creeks. Report spill to Coast Guard toll free number (800) 424-8802. In case of accident or road spill notify CHEMTREC (800) 424-9300.

**PROCEDURES IF MATERIAL IS RELEASED OR SPILLED:** Adsorb on fire retardant treated sawdust, diatomaceous earth, etc. Shovel up and dispose of at an appropriate waste disposal facility in accordance with current applicable laws and regulations, and product characteristics at time of disposal.

**ENVIRONMENTAL PRECAUTIONS:** Prevent spills from entering storm sewers or drains and contact with soil.

**PERSONAL PRECAUTIONS:** See Section 8

---

## 7. HANDLING AND STORAGE

---

**HANDLING:** No special precautions are necessary beyond normal good hygiene practices. See Section 8 for additional personal protection advice when handling this product.

**STORAGE:** Do not store in open or unlabelled containers. Store away from strong oxidizing agents or combustible material.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**VENTILATION:** No special requirements under ordinary conditions of use and with adequate ventilation.

**RESPIRATORY PROTECTION:** No special requirements under ordinary conditions of use and with adequate ventilation.

**EYE PROTECTION:** Normal industrial eye protection practices should be employed.

**SKIN PROTECTION:** No special equipment required. However, good personal hygiene practices should always be followed.

**EXPOSURE LIMITS:** This product does not contain any components which have recognized exposure limits. However, a exposure limit of 5.00 mg/m<sup>3</sup> is suggested for oil mist.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

Typical physical properties are given below. Consult Product Data Sheet for specific details.

**APPEARANCE:** Liquid

**COLOR:** Slightly Hazy Amber

**ODOR:** Mild

**ODOR THRESHOLD-ppm:** NE

pH: NA  
BOILING POINT C(F): > 316(600)  
MELTING POINT C(F): NA  
FLASH POINT C(F): > 204(400) (ASTM D-92)  
FLAMMABILITY: NE  
AUTO FLAMMABILITY: NE  
EXPLOSIVE PROPERTIES: NA  
OXIDIZING PROPERTIES: NA  
VAPOR PRESSURE-mmHg 20 C: < 0.1  
VAPOR DENSITY: > 2.0  
EVAPORATION RATE: NE  
RELATIVE DENSITY, 15/4 C: 0.894  
SOLUBILITY IN WATER: Negligible  
PARTITION COEFFICIENT: > 3.5  
VISCOSITY AT 40 C, cSt: 220.0  
VISCOSITY AT 100 C, cSt: 19.5  
POUR POINT C(F): -18(0)  
FREEZING POINT C(F): NE  
VOLATILE ORGANIC COMPOUND: NA  
NA=NOT APPLICABLE NE=NOT ESTABLISHED D=DECOMPOSES  
FOR FURTHER TECHNICAL INFORMATION, CONTACT YOUR MARKETING REPRESENTATIVE

---

## 10. STABILITY AND REACTIVITY

---

STABILITY (THERMAL, LIGHT, ETC.): Stable.  
CONDITIONS TO AVOID: Extreme heat.  
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers.  
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide. Elemental oxides  
Metal oxides.  
HAZARDOUS POLYMERIZATION: Will not occur.

---

## 11. TOXICOLOGICAL DATA

---

### ---ACUTE TOXICOLOGY---

ORAL TOXICITY (RATS): Practically non-toxic (LD50: greater than 2000 mg/kg). ---Based on testing of similar products and/or the components.  
DERMAL TOXICITY (RABBITS): Practically non-toxic (LD50: greater than 2000 mg/kg). ---Based on testing of similar products and/or the components.  
INHALATION TOXICITY (RATS): Practically non-toxic (LC50: greater than 5 mg/l). ---Based on testing of similar products and/or the components.  
EYE IRRITATION (RABBITS): Practically non-irritating. (Draize score: 0 or greater but 6 or less). ---Based on testing of similar products and/or the components.  
SKIN IRRITATION (RABBITS): Practically non-irritating. (Primary Irritation Index: greater than 0.5 but less than 3). ---Based on testing of similar products and/or the components.  
OTHER ACUTE TOXICITY DATA: The acute toxicological results summarized above are based on testing of representative Mobil products. Representative Mobil formulations have shown no acute effects, administered via the inhalation route, when tested at maximum attainable oil mist or vapor concentrations.

### ---SUBCHRONIC TOXICOLOGY (SUMMARY)---

Severely solvent refined and severely hydrotreated mineral base oils have been tested at Mobil Environmental and Health Sciences Laboratory by dermal application to rats 5 days/week for 90 days at doses significantly higher than those expected during normal industrial exposure. Extensive evaluations including microscopic

examination of internal organs and clinical chemistry of body fluids, showed no adverse effects.

---CHRONIC TOXICOLOGY (SUMMARY)---

The base oils in this product are severely solvent refined and/or severely hydrotreated. Chronic mouse skin painting studies of severely treated oils showed no evidence of carcinogenic effects. These results are confirmed on a continuing basis using various screening methods such as the Mobil Modified Ames Test and IP-346.

---SENSITIZATION (SUMMARY)---

Representative Mobil formulations have not caused skin sensitization in guinea pigs.

---

## 12. ECOLOGICAL INFORMATION

---

ENVIRONMENTAL FATE AND EFFECTS: This product is expected to be inherently biodegradable. There is no evidence to suggest bioaccumulation will occur.

Acute LC/EC50: Juvenile Rainbow Trout: Practically non-toxic

---Based on testing of similar products.

Accidental spillage may lead to penetration in the soil and groundwater. However, there is no evidence that this would cause adverse ecological effects.

---

## 13. DISPOSAL CONSIDERATIONS

---

WASTE DISPOSAL: Product is suitable for burning in an enclosed, controlled burner for fuel value or disposal by supervised incineration. Such burning may be limited pursuant to the Resource Conservation and Recovery Act. In addition, the product is suitable for processing by an approved recycling facility or can be disposed of at an appropriate government waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

RCRA INFORMATION: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity, or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

---

## 14. TRANSPORT INFORMATION

---

USA DOT: NOT REGULATED BY USA DOT.

RID/ADR: NOT REGULATED BY RID/ADR.

IMO: NOT REGULATED BY IMO.

IATA: NOT REGULATED BY IATA.

---

## 15. REGULATORY INFORMATION

---

Governmental Inventory Status: All components comply with TSCA, EINECS/ELINCS, AICS, and DSL.

EU Labeling: EU labeling not required.

U.S. Superfund Amendments and Reauthorization Act (SARA) Title III:  
 This product contains no "EXTREMELY HAZARDOUS SUBSTANCES".  
 SARA (311/312) REPORTABLE HAZARD CATEGORIES: None.  
 This product contains no chemicals reportable under  
 SARA (313) toxic release program.

THIS PRODUCT HAS BEEN AUTHORIZED BY USDA FOR USE UNDER THE FOLLOWING  
 CATEGORY: H2 - Lubricants With No Food Contact

The following product ingredients are cited on the lists below:

CHEMICAL NAME	CAS NUMBER	LIST CITATIONS
---------------	------------	----------------

-----  
 \*\*\* NO REPORTABLE INGREDIENTS \*\*\*  
 --- REGULATORY LISTS SEARCHED ---  
 1=ACGIH ALL 6=IARC 1 11=TSCA 4 16=CA P65 CARC 21=LA RTK  
 2=ACGIH A1 7=IARC 2A 12=TSCA 5a2 17=CA P65 REPRO 22=MI 293  
 3=ACGIH A2 8=IARC 2B 13=TSCA 5e 18=CA RTK 23=MN RTK  
 4=NTP CARC 9=OSHA CARC 14=TSCA 6 19=FL RTK 24=NJ RTK  
 5=NTP SUS 10=OSHA Z 15=TSCA 12b 20=IL RTK 25=PA RTK  
 26=RI RTK

Code key: CARC=Carcinogen; SUS=Suspected Carcinogen; REPRO=Reproductive

-----  
**16. OTHER INFORMATION**  
 -----

USE: INDUSTRIAL GEAR OIL

NOTE: MOBIL PRODUCTS ARE NOT FORMULATED TO CONTAIN PCBS.

-----  
 Please call the Customer Response Center on 800-662-4525 for formulation  
 disclosure.

\*\*\*\*\*  
 For Internal Use Only: MHC: 1\* 1\* 0\* 0\* 1\*, MPPEC: A, TRN: 610873-00,  
 GLIS: 400352, CMCS97: 970984, REQ: US - MARKETING, SAFE USE: L  
 EHS Approval Date: 08NOV1999  
 \*\*\*\*\*

\*\*\*\*\*  
 Legally required information is given in accordance with applicable  
 Information given herein is offered in good faith as accurate, but  
 without guarantee. Conditions of use and suitability of the product for  
 particular uses are beyond our control; all risks of use of the product  
 are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL  
 WARRANTIES OF EVERY KIND AND NATURE, INCLUDING WARRANTIES OF  
 MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE IN RESPECT TO  
 THE USE OR SUITABILITY OF THE PRODUCT. Nothing is intended as a  
 recommendation for uses which infringe valid patents or as extending  
 any license under valid patents. Appropriate warnings and safe handling  
 procedures should be provided to handlers and users. Use or re-  
 transmission of the information contained herein in any other format  
 than the format as presented is strictly prohibited. Mobil neither  
 represents nor warrants that the format, content or product formulas  
 contained in this document comply with the laws of any other country  
 except the United States of America.  
 \*\*\*\*\*

Copyright 1996 Mobil Corporation, All rights reserved