



PERFORMANCE STARTS HERE

LBB-1660

MANUAL HONE FOR PRECISION ROD RECONDITIONING



SUNNEN'S LBB-1660 HONE: GETS YOU INTO H



THE SUNNEN® ROD HONING METHOD IS PREFERRED FOR PRECISION - WORLDWIDE.

The LBB-1660 produces a round and straight honed bore ... in all respects equal to or better than manufacturer's new rods.



You can keep your rod inventory at a minimum and provide fast turnaround service on your customers' own rods.

Honing units are available for complete rod reconditioning diameter ranges of 1.450 in. to 4.700 in. (36,9 - 119,4 mm).

PIN FITTING PRECISION, TOO!

The LBB-1660 hones both piston pin holes at the same time for perfect center line alignment of the holes ... as important as hole size!

Pin fitting with the LBB-1660 will give you pre-run-in fit with full bearing surface.

You can expect accuracy to .0001 in. (.0025 mm) with the Sunnen LBB-1660.

Mandrels from .370 in. to 2.625 in. (9,4 - 66,7 mm) are available for pin fitting and other automotive jobs.

HIGH PROFIT ROD RECONDITIONING



ONLY A FEW JOBS PER MONTH WILL PAY FOR YOUR SUNNEN LBB-1660 HONE AND GAGE.

A ready-made market! Rods should be reconditioned on every major overhaul and engine rebuild. And the Sunnen LBB-1660 is the method your customers know and trust.

You make more money faster and easier reconditioning rods with the Sunnen LBB-1660 than most other shop operations. You do a set of eight rods in less than 40 minutes.

Increases parts sales. You get an extra profit bonus from additional parts sales of related items on every job.

And it is versatile. In addition to rod reconditioning, the Sunnen LBB-1660 does King Pins, air compressors and small bore engines like those found on motorcycles, boats and lawn mowers.



**THE LBB-1660,
BUILT AND BACKED BY
SUNNEN, THE LEADER IN
AUTOMOTIVE HONING**

SIX SPEED V- BELT DRIVE

Provides optimum speed for a wide range of diameters ... 200 -640 rpm.

POWERFUL ELECTRIC MOTOR with enough power to recondition larger rods.

AG-400 PRECISION GAGE & GAGE STAND (OPTIONAL)

The most widely accepted gage in the industry and for good reason! It's rugged, reliable and accurate. Reads in "tenths" - .0001 in. (.0025 mm).

GAGE SETTING FIXTURE (OPTIONAL)

Transfers pin size from the pin to the AG-400 Precision Gage. Eliminates discrepancies between the size of setting masters and parts being honed.

DUAL CUTTING PRESSURE DIALS

Light and heavy cutting pressure dials give you the optimum adjustability for good stock removal rates with maximum stone life. (Heavy cutting pressure dial not visible.)

THE LBB IS NOW EQUIPPED WITH NEW SAFETY FEATURES INCLUDING A SPINDLE MOTOR BRAKE, AN INTERLOCKED BELT GUARD, A LOCKABLE COOLANT ACCESS DOOR AND A FOOT GUARD.



A detailed view of the Sunnen LBB-1660 Honing Machine. The machine is white with a black honing head assembly. A red line points from the text to the stone feed mechanism. Another red line points from the text to the oil delivery system. A third red line points from the text to the oil tank. A fourth red line points from the text to the pedal bar. The machine is shown from a three-quarter perspective, highlighting its industrial design and various adjustment points.

PRECISION STONE FEED UP SYSTEM

Accurate stone feed up for precise stone wear compensation.

DRIP TRAYS (OPTIONAL)

Provide work surface for in-process parts and allow honing oil to drain for re-use. (Two drip trays are included in optional CRF-100 Connecting Road kit.)

ADJUSTABLE THREE JET HONING OIL DELIVERY SYSTEM

Easily adjusted to assure even flow of honing oil over the part being honed and the entire mandrel.

SELF CONTAINED OIL TANK

Holds 15 gallons (58.8L) of Sunnen Honing Oil.

ADJUSTABLE PEDAL BAR

Length is adjustable for maximum operator comfort.

Pictured with optional worklight.

THE COMPLETE SUNNEN ROD RECONDITIONING PACKAGE

Sunnen provides everything you need to start making money right away! Just order the following:

1. LBB-1660 Honing Machine

Shipped assembled and ready for operation with a minimum of setup required. Includes:

- MAN-700 Diamond Dresser
- LBN-740 Work Support
- LBN-730 V-8 Con-Rod Support
- LN-0116A Eccentric Sleeve

2. AG-400 Precision Gage

The AG-400 is the industry standard for precision gaging (order separately). Assures accuracy within .0001 in. (.0025 mm) with a range of .375 in. - 3.375 in. (9.5 - 85.7 mm) with optional point sets.

3. MAN-845-5 Five Gallon (18.9 L) Honing Oil

Use genuine Sunnen Honing Oil for faster cutting, maximum stone life and finest surface finish. Machine requires 15 gallons (56.8 L). (Order separately.)

4. Tooling and Accessories

Select Sunnen-manufactured mandrels, stones and accessories to fit your exact applications. No one offers a more complete package than Sunnen.

SUNNEN LBB-1660 THE MOST VERSATILE MACHINE IN YOUR SHOP



PISTON PIN BORES - One of the most critical tolerances in engine rebuilding. Make sure pin holes are perfectly aligned and to size with Sunnen honing. You may even want to "touch up" factory-new piston pin holes to meet your specs.



SMALL BORE ENGINES - Sunnen honing makes quick work of whatever kind of small bore engines you work on ... motorcycles, lawn mowers, chain saw, garden tractor ... single or multiple-cylinder, two- or four-stroke.




KING PIN BORES - Even lower volume operations such as king pin rebuilding can be profitable with the versatile Sunnen LBB-1660.

SUNNEN-MADE ABRASIVES

From aluminum oxide to silicon carbide to diamond and CBN, Sunnen manufactures the industry's largest variety of abrasives, bond types, grain sizes and stone configurations.

Before any stone is shipped, it is graded and qualified, maintaining the most exacting quality control standards in the industry to assure you of the most precise and consistent honing performance available.

Since 1924, Sunnen has been the leader in honing. We constantly improve our automotive honing systems by incorporating the same technology we put into our high-production, automated systems used by OEM engine component manufacturers. Sunnen systems are reliable, durable and flexible and are designed to deliver the precision our customers have grown to expect.



SPECIFICATIONS:

SPINDLE SPEED:

200 to 640 rpm

SPINDLE MOTOR:

.5 Hp (.37 kw)

DIAMETER RANGE (ID):

Manual Stroking- .370 -4.700 in.

(9.4 - 119 mm)

With CRF-100 Stroking Kit: 1,450 - 3.300 in.

(37-84 mm)

HONING OIL PUMP:

Centrifugal pump driven from the spindle motor

HONING OIL CAPACITY:

15 gallons (58.8 L)

ELECTRICAL SYSTEM OPTIONS:

MODEL NUMBERS

LBB1660CK 115 V 60 Hz SINGLE PHASE

LBB1660CE 460 V 60 Hz 3 PHASE

LBB1660CD 230 V 60 Hz 3 PHASE

LBB1660CG CE/400 V 50 Hz 3 PHASE

LBB1660CH CE/440 V 50 Hz 3 PHASE

ALL MODELS CE COMPLIANT

FLOORSPACE:

27.5 in. wide by 28.25 in. deep by 62.5 high
(700 mm by 730 mm by 1590 mm)

SHIPPING WEIGHT:

Approximately 675 pounds (306 kg)

OPTIONAL CRF-100 MANUAL STROKING KIT FOR CONSISTENTLY STRAIGHT BORES ROD AFTER ROD

This kit provided controlled hand stroking of connecting rod on a special fixture and gives many advantages over conventional hand stroking. It can be factory installed when order or retrofitted in the field.

TOOLING

Sunnen offers a wide range of tooling for connecting rod reconditioning.



SRT tools deliver excellent accuracy with Sunnen diamond or CBN abrasive stones.

CR Honing Units are specially designed for honing con rod bores to original size on low-to-mid-volume rod reconditioning machines.

SUNNEN PREMIUM HONING OILS & COOLANTS

Sunnen's premium honing oils and coolants provide extreme lubricity for higher honing pressure and harder abrasives, delivering faster, lower cost-per-part and ultimately more profitable cutting rates.





A LEGACY OF EXCELLENCE SINCE 1924.

WORLDWIDE

Our global manufacturing, distribution, and sales and service network allows us to deliver quality Sunnen solutions worldwide.

And our state-of-the-art Technical Services Centers allow our technical experts to develop innovative solutions to customer application challenges. The Centers also provide answers for customer questions and training for Sunnen representatives around the world.

SUNNEN PRODUCTS COMPANY WORLD HEADQUARTERS St. Louis, MO – USA

Phone 1.314.781.2100
Fax 1.314.781.2268
Toll Free 1.800.325.3670
Email sunnen@sunnen.com
www.sunnen.com



AUSTRIA - SUNNEN AUSTRIA GMBH HOHENEMS

Phone +43 (0) 5576 74194
Fax +43 (0) 5576 74196
Email sales@sunnen.eu
www.sunnen.at Sunnen

BELGIUM - SUNNEN BENELUX BVBA KONTICH

Phone +32 38 80 2800
Fax +32 38 44 3901
Email info@sunnen.be
www.sunnen.be

BRAZIL - SUNNEN DO BRASIL LTDA. SÃO PAULO

Phone +55 11 4177-3824
Fax +55 11 4362-3083
Email sunnen@sunnen.com.br
www.sunnen.com.br

CHINA - SHANGHAI SUNNEN MECHANICAL CO. LTD.

SHANGHAI
Phone +86 21 5813 3990
FAX +86 21 5813 2299
Email shsunnen@sunnensh.com
www.sunnensh.com

CZECH REPUBLIC - SUNNEN S.R.O. STRAKONICE

Phone +420 383 376 317
Fax +420 383 376 316
Email sunnen@sunnen.cz
www.sunnen.cz

FRANCE - SUNNEN SAS

SACLAY
Phone +33 169 30 00 00
Fax +33 169 30 11 11
Email info@sunnen.fr
www.sunnen.fr

INDIA - SUNNEN INDIA PVT. LTD. MUMBAI

Phone +91 223 913 6055
Fax +91 223 913 6056
Email sales@sunnen.in
www.sunnen.in

ITALY - SUNNEN ITALIA S.R.L. ARESE

Phone +39 02 383 417 1
Fax +39 02 383 417 50
Email sunnen@sunnenitalia.com
www.sunnenitalia.com

POLAND - SUNNEN POLSKA SP. Z O.O. WARSZAWA

Phone +48 22 814 34 29
Fax +48 22 814 34 28
Email sunnen@sunnen.pl
www.sunnen.pl

SUNNEN RUS LLC

MOSCOW – RUSSIA
Phone +7 495 258 43 43
Fax +7 495 258 91 75
Email sunnen@sunnen-russia.ru
www.sunnen.ru

SWITZERLAND - SUNNEN AG ENNETAACH

Phone +41 71 649 33 33
Fax +41 71 649 33 34
Email sales@sunnen.eu
www.sunnen.eu

UK - SUNNEN PRODUCTS LTD. HEMPSTEAD HERTS

Phone +44 1442 39 39 39
Fax +44 1442 39 12 12
Email hemel@sunnen.co.uk
www.sunnen.co.uk

Sunnen reserves the right to change or revise specifications and product design in connection with any feature of our products contained herein. Such changes do not entitle the buyer to corresponding changes, improvements, additions, or replacements for equipment, supplies or accessories previously sold. Information contained herein is considered to be accurate based on available information at the time of printing. Should any discrepancy of information arise, Sunnen recommends that user verify the discrepancy with Sunnen before proceeding.