



SAFETY DATA SHEET

Issuing Date 20-Oct-2014

Revision Date 30-Jun-2020

Revision Number 2

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name GUIDE SHOE, MANDREL, TRUING SLEEVE, ALIGNMENT BUSHING and TS Shot

Other means of identification

Part Number VARIOUS

Synonyms PRODUCT IDENTIFIER SDS-001

Recommended use of the chemical and restrictions on use

Recommended Use Tooling used in the honing process

Uses advised against No information available

Supplier's details

Supplier Address

Sunnen Products
7910 Manchester
Saint Louis, MO 63143
314-781-2100
Website: www.sunnen.com

Emergency telephone number 1 (314) 781-2100 8 a. m. - 3 p.m. C.S.T (US)
Email: SDS@sunnen.com

2. HAZARDS IDENTIFICATION

Classification

Downstream use of this product, results in hazardous elements being emitted under certain processing conditions such as but not limited to: abrading, cutting, welding, sanding, burning, milling or grinding. The classifications given below pertains to when used during these processes.

Respiratory Sensitization	Category 1
Skin Sensitization	Category 1
Carcinogenicity	Category 1B
Specific Target Organ Toxicity (Repeated Exposure)	Category 1

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word	Danger
--------------------	---------------

Hazard Statements

May cause allergic reactions upon breathing of dusts
 May cause allergic skin reactions
 May cause eye irritation
 Causes damage to aquatic life upon repeated exposure



Appearance Various shades, Black,
Silver, Brass

Physical State Solid.

Odor No information available

Precautionary Statements**Prevention**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- In case of inadequate ventilation wear respiratory protection.
- Contaminated work clothing should not be allowed out of the workplace.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wash face, hands and any exposed skin thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Do not eat, drink or smoke when using this product.

General Advice

- If exposed or concerned: Get medical attention/advice

Skin

- IF ON SKIN: Wash with plenty of soap and water.
- If skin irritation or rash occurs: Get medical advice/attention.
- Wash contaminated clothing before reuse.

Inhalation

- IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing
- If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Storage

- Store locked up.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

Very toxic to aquatic life Very toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms

PRODUCT IDENTIFIER SDS-001

Chemical Name	CAS-No	Weight %	Trade secret
Iron	7439-89-6	0-100	*
Zinc	7440-66-6	0-96	*

Copper (metallic)	7440-50-8	0-85	*
Aluminum	7429-90-5	0-12	*
Nickel	7440-02-0	0-3	*
Manganese	7439-96-5	0-2	*
Chromium	7440-47-3	0-2	*
Cobalt	7440-48-4	<1.5	*
Vanadium	7440-62-2	0-1	*
Sulfur	7704-34-9	0-1	*
Silicon	7440-21-3	0-1	*
Phosphorous acid	13598-36-2	0-1	*
Molybdenum	7439-98-7	0-1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

General Advice	If exposed or concerned: Get medical attention/advice
Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin Contact	Wash skin with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Contaminated clothing presents a fire hazard and should be removed immediately.
Inhalation	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
Ingestion	Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects Asthma-like and/ or skin allergy-like symptoms. Difficulty in breathing. Coughing and/ or wheezing. Rashes

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician May cause sensitization of susceptible persons.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media None

Specific Hazards Arising from the Chemical

None known

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Downstream use of this product, results in hazardous elements being emitted under certain processing conditions such as but not limited to: abrading, cutting, welding, sanding, burning, milling or grinding. In these case, the following precautions should be taken. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

Environmental Precautions**Environmental Precautions**

Avoid release to the environment metal fines produced from abrading, cutting, welding, sanding, burning, milling or grinding.

Methods and materials for containment and cleaning up**Methods for Containment**

Not applicable

Methods for Cleaning Up

Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE**Precautions for safe handling****Handling**

If exposed to dust: In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities**Storage**

Store in accordance with local regulations.

Incompatible Products

None known based on information supplied.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Control parameters****Exposure Guidelines**

Occupational exposure limits apply to some of the components resulting from abrading, cutting or grinding producing dust or fumes.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Copper (metallic) 7440-50-8	TWA: 0.2 mg/m ³ fume	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Nickel 7440-02-0	TWA: 1.5 mg/m ³	TWA: 1 mg/m ³ (vacated) TWA: 1 mg/m ³	IDLH: 10 mg/m ³ TWA: 0.015 mg/m ³
Manganese 7439-96-5	TWA: 0.2 mg/m ³	(vacated) TWA: 1 mg/m ³ fume (vacated) STEL: 3 mg/m ³ fume (vacated) Ceiling: 5 mg/m ³ Ceiling: 5 mg/m ³ fume	IDLH: 500 mg/m ³ TWA: 1 mg/m ³ fume STEL: 3 mg/m ³
Cobalt 7440-48-4	TWA: 0.02 mg/m ³	TWA: 0.1 mg/m ³ dust and fume (vacated) TWA: 0.05 mg/m ³ dust and fume	IDLH: 20 mg/m ³ dust and fume TWA: 0.05 mg/m ³ dust and fume

Silicon 7440-21-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Molybdenum 7439-98-7	TWA: 10 mg/m ³ inhalable fraction TWA: 3 mg/m ³ respirable fraction	(vacated) TWA: 10 mg/m ³	IDLH: 5000 mg/m ³
Vanadium 7440-62-2	-	(vacated) TWA: 0.05 mg/m ³ V2O5 respirable dust (vacated) TWA: 0.05 mg/m ³ V2O5 fume Ceiling: 0.5 mg/m ³ V2O5 respirable dust Ceiling: 0.1 mg/m ³ V2O5 fume	Ceiling: 0.05 mg/m ³ V dust and fume 15 min TWA: 1 mg/m ³ STEL: 3 mg/m ³ Ferrovandium dust

Appropriate engineering controls**Engineering Measures**

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Always wear approved safety glasses with side shields when operating machinery.

Skin and Body Protection

Wear protective gloves/clothing.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Solid	Appearance	Various shades Black Silver Brass
Odor	No information available	Odor Threshold	No information available
Property	Values	Remarks/ - Method	
pH	Not applicable	None known	
Melting Point/Range	Not applicable	None known	
Boiling Point/Boiling Range	Not applicable	None known	
Flash Point	Not applicable.	None known	
Evaporation rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limits in Air			
upper flammability limit	No data available		
lower flammability limit	No data available		
Vapor Pressure	No data available	None known	
Vapor Density	No data available	None known	
Specific Gravity		None known	
Water Solubility	Not applicable	None known	
Solubility in other solvents	Not applicable	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition Temperature	No data available	None known	
Decomposition Temperature	No data available	None known	
Viscosity	Not applicable	None known	
Flammable Properties	Not flammable		
Explosive Properties	No data available		
Oxidizing Properties	No data available		

Other information

VOC Content (%) No data available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Dust formation.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information****Inhalation**

Product does not present an acute toxicity hazard based on known or supplied information. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Inhalation of dust in high concentration may cause irritation of respiratory system.

Eye Contact

Dust contact with the eyes can lead to mechanical irritation.

Skin Contact

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Ingestion

Not an expected route of exposure.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Carbon	10000 mg/kg (Rat)	-	-
Sulfur	> 3000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 9.23 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics**Symptoms**

Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing

Delayed and immediate effects and also chronic effects from short and long term exposure**Sensitization**

May cause sensitization by inhalation. May cause sensitization by skin contact.

Mutagenic Effects

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Nickel		Group 2B	Reasonably Anticipated	X
Chromium		Group 3		
Cobalt	A3	Group 2B	Reasonably Anticipated	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3: Not Classifiable as to its Carcinogenicity to Humans

NTP: (National Toxicity Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure if inhaled

Aspiration Hazard

No information available.

Numerical measures of toxicity - Product

The following values are calculated based on chapter 3.1 of the GHS document: Not applicable

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Iron 7439-89-6	-	LC50 96 h: = 0.56 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 13.6 mg/L static (Morone saxatilis)	-	-
Zinc 7440-66-6	EC50 72 h: 0.09 - 0.125 mg/L static (Pseudokirchneriella subcapitata) EC50 96 h: 0.11 - 0.271 mg/L static (Pseudokirchneriella subcapitata)	LC50 96 h: 0.211-0.269 mg/L semi-static (Pimephales promelas) LC50 96 h: 2.16-3.05 mg/L flow-through (Pimephales promelas) LC50 96 h: = 0.24 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 0.41 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 0.45 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 0.59 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: = 2.66 mg/L static (Pimephales promelas) LC50 96 h: = 3.5 mg/L static (Lepomis macrochirus) LC50 96 h: = 30 mg/L (Cyprinus carpio) LC50 96 h: = 7.8 mg/L static (Cyprinus carpio)		EC50 48 h: 0.139 - 0.908 mg/L Static (Daphnia magna)

Copper (metallic) 7440-50-8	EC50 96 h: 0.031 - 0.054 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: 0.0426 - 0.0535 mg/L static (Pseudokirchneriella subcapitata)	LC50 96 h: 0.0068 - 0.0156 mg/L (Pimephales promelas) LC50 96 h: < 0.3 mg/L static (Pimephales promelas) LC50 96 h: = 0.052 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 0.112 mg/L flow-through (Poecilia reticulata) LC50 96 h: = 0.2 mg/L flow-through (Pimephales promelas) LC50 96 h: = 0.3 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 0.8 mg/L static (Cyprinus carpio) LC50 96 h: = 1.25 mg/L static (Lepomis macrochirus)		EC50 48 h: = 0.03 mg/L Static (Daphnia magna)
Nickel 7440-02-0	EC50 72 h: = 0.18 mg/L (Pseudokirchneriella subcapitata) EC50 96 h: 0.174 - 0.311 mg/L static (Pseudokirchneriella subcapitata)	LC50 96 h: > 100 mg/L (Brachydanio rerio) LC50 96 h: = 1.3 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 10.4 mg/L static (Cyprinus carpio)	-	EC50 48 h: > 100 mg/L (Daphnia magna) EC50 48 h: = 1 mg/L Static (Daphnia magna)
Cobalt 7440-48-4	-	LC50 96 h: > 100 mg/L static (Brachydanio rerio)	-	-
Phosphorous acid 13598-36-2		LC50 96 h: 6980 - 9784 mg/L static (Brachydanio rerio)		
Sulfur 7704-34-9	-	LC50: 866 mg/L Brachydanio rerio 96 h static LC50: <14 mg/L Lepomis macrochirus 96 h static LC50: >180 mg/L Oncorhynchus mykiss 96 h static	-	-

Persistence and Degradability No information available.

Bioaccumulation No information available.

Other Adverse Effects
No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Do not re-use empty containers.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Nickel - 7440-02-0	(hazardous constituent - no waste number)	Included in waste streams: F006, F039		
Chromium - 7440-47-3		Included in waste streams: F032, F034, F035, F037, F038, F039	5.0 mg/L regulatory level	
Vanadium - 7440-62-2		Included in waste stream: F039		

14. TRANSPORT INFORMATION

<u>DOT</u>	Not regulated
<u>TDG</u>	Not regulated
<u>MEX</u>	Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Zinc	7440-66-6	96	1.0
Copper	7440-50-8	85	1.0
Aluminum	7429-90-5	12	1.0
Nickel	7440-02-0	3	0.1
Chromium	7440-47-3	2	1.0
Cobalt	7440-48-4	1.5	0.1
Vanadium	7440-62-2	1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc		X	X	
Copper (metallic)		X	X	
Nickel		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Zinc	1000 lb		RQ 454 kg final RQ RQ 1000 lb final RQ
Copper (metallic)	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

Chromium			RQ 5000 lb final RQ RQ 2270 kg final RQ
----------	--	--	--

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Nickel	7440-02-0	Carcinogen
Cobalt	7440-48-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Zinc	X	X	X		X
Copper	X	X	X	X	X
Aluminum	X	X	X		X
Nickel	X	X	X	X	X
Cobalt	X	X	X	X	X
Silicon	X	X	X		X
Vanadium	X	X	X		
Phosphorous acid	X				
Molybdenum	X	X	X		X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 0	Flammability 0	Instability 0	Physical and Chemical Hazards -
<u>HMIS</u>	Health Hazard 2*	Flammability 0	Physical Hazard 0	Personal Protection X

**Indicates a chronic health hazard.*

Prepared By Sunnen Products Company
7910 Manchester Road
Saint Louis, MO 63143
1-314-781-2100

Issuing Date 20-Oct-2014
Revision Date 30-Jun-2020
Revision Note Review

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet

Product label on following page.



DANGER

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Causes damage to organs through prolonged or repeated exposure. Appearance: Various shades, Black, Silver, Brass. Physical State: Solid Odor: None

FIRST AID

As a solid object the honing stone presents no hazard at normal temperatures. However when used in the normal manner or if modified for use by abrading, grinding, cutting or processing in another fashion that creates potentially hazardous dust or fumes can result in exposure by inhalation, swallowing or come in contact with skin or eyes. The information below is for these instances.

INHALATION: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. **SKIN CONTACT:** Wash skin with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Contaminated clothing presents a fire hazard and should be removed immediately. **EYE CONTACT:** Remove contact lenses if convenient to do so. Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Get medical attention if irritation persists. **INGESTION:** Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

IN CASE OF FIRE

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

HONING TOOLS

PRODUCT IDENTIFIER SDS-001

CONTAINS: <3% NICKEL CAS 7440-02-0, <1.5% COBALT CAS 7440-48-4, <1% SULFUR CAS 7440-21-3, <1% PHOSPHOROUS ACID CAS 13598-36-2

PRECAUTIONARY STATEMENTS

PREVENTION: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. In case of inadequate ventilation wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. **GENERAL ADVICE:** If exposed or concerned: Get medical attention/advice. **SKIN:** IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. **INHALATION:** IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

STORAGE: Store locked up. **DISPOSAL:** Dispose of contents/container to an approved waste disposal plant. **HAZARD NOT OTHERWISE CLASSIFIED (HNOC):** Not applicable. **OTHER INFORMATION:** Very toxic to aquatic life with long lasting effects.

SUNNEN PRODUCTS
7910 MANCHESTER AVE. ST.
LOUIS, MO 63143 U.S.A.
314-781-2105

LAB-001-US(en)-HONING TOOLS 20150416