



SAFETY DATA SHEET

Issuing Date 14-May-2015

Revision Date 30-Jun-2020

Revision Number 3

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Vitrified or Resin Bond Abrasive Honing Stone or PHT / DB Abrasive Brush

Other means of identification

Synonyms Product Identifier SDS084

Recommended use of the chemical and restrictions on use

Recommended Use Abrasive tool used in honing.

Uses advised against No information available

Supplier's details

Supplier Address

Sunnen Products
7910 Manchester
Saint Louis, MO 63143
314-781-2100
Website: www.sunnen.com

Emergency telephone number

Emergency Telephone Number 1 (314) 781-2100 8 a. m. - 3 p.m. C.S.T (US)
Email: SDS@sunnen.com

2. HAZARDS IDENTIFICATION

Classification

Downstream use of this product, results in hazardous elements being emitted under certain processing conditions such as but not limited to: abrading, cutting, welding, sanding, burning, milling or grinding. The classifications given below pertain to when used during these processes.

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Carcinogenicity	Category 1A
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3
Specific Target Organ Toxicity (Repeated Exposure)	Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word Danger

Hazard Statements

- Causes skin irritation
- Causes serious eye irritation
- May cause cancer
- May cause respiratory irritation
- May cause damage to organs through prolonged or repeated exposure

**Appearance** No information available**Physical State** No information available.**Odor** No information available**Precautionary Statements****Prevention**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Wash face, hands and any exposed skin thoroughly after handling.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- If exposed or concerned: Get medical attention/advice

Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

Skin

- IF ON SKIN: Wash with plenty of soap and water.
- If skin irritation occurs: Get medical advice/attention.
- Take off contaminated clothing and wash before reuse.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Storage

- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

Harmful to aquatic life with long lasting effects

.?% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Synonyms**

Product Identifier SDS084

Chemical Name	CAS-No	Weight %	Trade secret
Silicon carbide	409-21-2	0-96	*
Aluminum oxide	1344-28-1	0-96	*
Sulfur	7704-34-9	0-45	*
Phenol-formaldehyde polymer	9003-35-4	0-30	*
Chemical Frits (Lead Free)	65997-18-4	10-15	*
Silica, fused	60676-86-0	0-10	*
Quartz	14808-60-7	0-8.75	*
Kaolin	1332-58-7	0-7.45	*
Titanium dioxide	13463-67-7	0-5.25	*
Silicon Dioxide - hydrated	7631-86-9	0-4.83	*
Iron oxide	1309-37-1	0-4.83	*
Silica, cristobalite	14464-46-1	0-4.38	*
Chromium (III) oxide	1308-38-9	0-1.84	*
Urea formaldehyde polmer	9011-05-6	0-1.7	*
Aluminum	7429-90-5	0-1.65	*
Limestone	1317-65-3	0-0.81	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

General Advice As a solid object the honing stone presents no hazard at normal temperatures. However if modified for use by abrading, grinding, cutting or processing in another fashion that creates potentially hazardous dust or fumes can result in exposure by inhalation, swallowing or come in contact with skin or eyes. The information below is for these instances.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation persists.

Skin Contact Wash skin with soap and water. Get medical attention if irritation persists.

Inhalation IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing

Ingestion IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects Irritation

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media None

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors.

Explosion Data

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid dust formation. Avoid inhalation of dust. Avoid contact with skin, eyes and clothing. Use personal protective equipment.

Environmental Precautions

Environmental Precautions Avoid release to the environment. Collect spillage. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment None required.

Methods for Cleaning Up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling None required under normal usage. If exposed to dust: Avoid dust formation. Ensure adequate ventilation. Do not breathe dusts or fumes. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Store in accordance with the particular national regulations

Incompatible Products Acids, Bases, Strong oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines Occupational exposure limits apply to some of the components resulting from abrading, cutting or grinding producing dust or fumes.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Aluminum oxide 1344-28-1	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	-
Silicon carbide 409-21-2	TWA: 10 mg/m ³ nonfibrous, inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica TWA: 3 mg/m ³ nonfibrous, respirable fraction, particulate matter containing no asbestos and <1% crystalline silica TWA: 0.1 fiber/cm ³ respirable fibers, including whiskers, length >5 µm, aspect ratio ≥3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination.	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust

Chemical Frits (Lead Free) 65997-18-4	STEL: 10 mg/m ³ Zr TWA: 0.01 mg/m ³ Cd TWA: 0.002 mg/m ³ Cd respirable fraction TWA: 0.5 mg/m ³ Sb TWA: 1 mg/m ³ Cu dust and mist TWA: 5 mg/m ³ Zr TWA: 0.02 mg/m ³ Mn TWA: 0.1 mg/m ³ Mn	TWA: 0.5 mg/m ³ Sb TWA: 5 mg/m ³ Zr Action Level: 5 µg/m ³ As Action Level: 30 µg/m ³ Pb Poison, See 29 CFR 1910.1025 Action Level: 2.5 µg/m ³ Cd (vacated) TWA: 0.5 mg/m ³ Sb (vacated) TWA: 5 mg/m ³ Zr (vacated) STEL: 10 mg/m ³ Zr (vacated) Ceiling: 5 mg/m ³ Mn Ceiling: 5 mg/m ³ Mn	IDLH: 5 mg/m ³ As IDLH: 9 mg/m ³ Cd dust and fume IDLH: 50 mg/m ³ Sb IDLH: 100 mg/m ³ Cu dust and mist IDLH: 500 mg/m ³ Mn IDLH: 25 mg/m ³ Zr IDLH: 100 mg/m ³ Ceiling: 0.002 mg/m ³ As 15 min Ceiling: 0.05 mg/m ³ V dust and fume 15 min TWA: 0.5 mg/m ³ Sb TWA: 1 mg/m ³ Cu dust and mist TWA: 1 mg/m ³ Mn TWA: 5 mg/m ³ except Zirconium tetrachloride Zr TWA: 0.050 mg/m ³ Except as Nickel Carbonyl Ni STEL: 3 mg/m ³ Mn STEL: 10 mg/m ³ Zr
Feldspar 68476-25-5	TWA: 10 mg/m ³ (inhal) 3 mg/m ³ (resp) PNO	TWA: 5 mg/m ³ (resp) 15 mg/m ³ (total) PNO	-
Silica, fused 60676-86-0	-	(vacated) TWA: 0.1 mg/m ³ respirable dust : (80)/(%) SiO ₂ mg/m ³ TWA TWA: 20 mppcf	-
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	30/(%SiO ₂ +2) mg/m ³ TWA, Total Dust; 250/(%SiO ₂ +5) mppcf TWA, respirable fraction; 10/(%SiO ₂ +2) mg/m ³ TWA, respirable TWA: 0.1 mg/m ³ (vacated)	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
Kaolin 1332-58-7	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated)	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
Iron oxide 1309-37-1	TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ fume (vacated) TWA: 10 mg/m ³ fume	IDLH: 2500 mg/m ³ Fe dust and fume TWA: 5 mg/m ³ Fe dust and fume
Silicon Dioxide - hydrated 7631-86-9	10 mg/m ³	20 mppcf TWA; ((80)/(%) SiO ₂) mg/m ³	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³
Silica, cristobalite 14464-46-1	TWA: 0.025 mg/m ³ respirable fraction	(vacated) TWA: 0.05 mg/m ³ respirable dust : (1/2)(30)/(%) SiO ₂ + 2 mg/m ³ TWA total dust : (1/2)(250)/(%) SiO ₂ + 5 mppcf TWA respirable fraction : (1/2)(10)/(%) SiO ₂ + 2 mg/m ³ TWA respirable fraction	IDLH: 25 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
Chromium (III) oxide 1308-38-9	TWA: 0.5 mg/m ³ Cr	TWA: 0.5 mg/m ³ Cr (vacated) TWA: 0.5 mg/m ³ Cr	IDLH: 25 mg/m ³ Cr(III) TWA: 0.5 mg/m ³ Cr
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated)	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Limestone 1317-65-3	-	TWA: 15 mg/m ³ TWA: 5 mg/m ³ (vacated) TWA: 15 mg/m ³ (vacated) TWA: 5 mg/m ³	TWA: 5 mg/m ³ respirable dust TWA: 10 mg/m ³ total dust

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Safety glasses with side-shields.
Skin and Body Protection	No protective equipment is needed under normal use conditions. Skin protection is not normally required for short exposures when honing with oil. Gloves and protective clothing should be worn if any operation generates dust.
Respiratory Protection	Not normally required when honing with oil. In the case of dust or aerosol formation use respirator with an approved filter.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical State	No information available.	Appearance	No information available.
Odor	No information available.	Odor Threshold	No information available.
Property	Values	Remarks/ - Method	
pH	No data available	None known	
Melting Point/Range	No data available	None known	
Boiling Point/Boiling Range	No data available	None known	
Flash Point	No data available	None known	
Evaporation rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limits in Air			
upper flammability limit	No data available		
lower flammability limit	No data available		
Vapor Pressure	No data available	None known	
Vapor Density	No data available	None known	
Specific Gravity	No data available	None known	
Water Solubility	No data available	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition Temperature	No data available	None known	
Decomposition Temperature	No data available	None known	
Viscosity	No data available	None known	
Flammable Properties	Not flammable		
Explosive Properties	No data available		
Oxidizing Properties	No data available		

Other information

VOC Content (%)	No data available
------------------------	-------------------

10. STABILITY AND REACTIVITY**Reactivity**

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

Acids, Bases, Strong oxidizing agents.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Product does not present an acute toxicity hazard based on known or supplied information. May cause irritation of respiratory tract. Inhalation of respirable particles of dust can cause lung fibrosis. Inhalation of fumes may cause metal fume fever, which is characterized by flu-like symptoms with metallic taste, fever, chills, cough, weakness, chest pain, muscle pain and increased white blood cell count.

Eye Contact

Causes serious eye irritation

Skin Contact

Causes skin irritation.

Ingestion

Not an expected route of exposure.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Sulfur	> 3000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 9.23 mg/L (Rat) 4 h
Phenol-formaldehyde polymer	> 5 g/kg (Rat)	> 2 g/kg (Rat)	-
Quartz	-	-	-
Titanium dioxide	> 10000 mg/kg (Rat)	-	-
Lithium carbonate	= 525 mg/kg (Rat)	-	> 2.17 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

Irritation

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization

No information available.

Mutagenic Effects

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Silicon carbide	A2			
Chemical Frits (Lead Free)	A1 A3 A2	Group 1 Group 2B Group 2A	Known Reasonably Anticipated	X
Silica, fused		Group 3		
Quartz	A2	Group 1	Known	X
Titanium dioxide		Group 2B	-	-
Silicon Dioxide - hydrated		Group 3		
Iron oxide		Group 3		
Silica, cristobalite	A2	Group 1		X
Chromium (III) oxide		Group 3		

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity

Some lithium ions and compounds have been shown to cause reproductive effects in animals. There is insufficient data to show if the lithium compounds present in this product will cause similar effects.

STOT - single exposure

May cause respiratory irritation

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure if inhaled

Aspiration Hazard

No information available.

Numerical measures of toxicity - Product**Acute Toxicity** .?% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document: Not applicable mg/L; Acute toxicity estimate

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Product in its current form (solid) is not likely to be a hazard to the environment. Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Sulfur 7704-34-9	-	LC50: 866 mg/L Brachydanio rerio 96 h static LC50: <14 mg/L Lepomis macrochirus 96 h static LC50: >180 mg/L Oncorhynchus mykiss 96 h static	-	-

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS**Waste Disposal Methods**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Where possible recycling is preferred to disposal or incineration.

Contaminated Packaging

Do not re-use empty containers.

14. TRANSPORT INFORMATION**DOT**

Not regulated

TDG

Not regulated

MEX

Not regulated

15. REGULATORY INFORMATION**International Inventories**

TSCA Complies
 DSL Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Chemical Frits (Lead Free)	65997-18-4	10-15	0.1 1.0
Feldspar	68476-25-5	12	1.0
Chromium (III) oxide	1308-38-9	1.84	1.0
Aluminum	7429-90-5	1.65	1.0
Lithium carbonate	554-13-2	0.1-1.0	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
 Chronic Health Hazard Yes
 Fire Hazard No
 Sudden Release of Pressure Hazard No
 Reactive Hazard No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Chemical Frits (Lead Free)		X		
Chromium (III) oxide		X		

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Chemical Frits (Lead Free)	65997-18-4	Carcinogen Developmental
Quartz	14808-60-7	Carcinogen
Titanium dioxide	13463-67-7	Carcinogen
Lithium carbonate	554-13-2	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Aluminum oxide	X	X	X		X
Silicon carbide	X	X	X		X
Sulfur	X	X	X		X
Lead compounds in chemical frits	X		X	X	X
Silica, fused	X	X			X
Quartz	X	X	X	-	X
Kaolin	X	X	X		X
Titanium dioxide		X			X
Iron oxide	X	X	X		X
Silica, cristobalite	X	X	X		
Chromium (III) oxide	X	X	X	X	X
Aluminum	X	X	X		X
Lithium carbonate	X	X			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health Hazard 1	Flammability 0	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 2*	Flammability 0	Physical Hazard 0	Personal Protection X

*Indicates a chronic health hazard.

Prepared By Sunnen Products Company
7910 Manchester Road
Saint Louis, MO 63143
1-314-781-2100

Issuing Date 14-May-2015
Revision Date 30-Jun-2020
Revision Note Review

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet



VITRIFIED/RESIN ABRASIVE

PRODUCT IDENTIFIER SDS-084

Conventional Abrasive Vitrified or Resin Bond (including Cork filled) Abrasive Honing Stone or Super-abrasive Vitrified Bond Abrasive Honing Stone or Conventional Abrasive Vitrified Bond Grinding Wheel or Abrasive De-burring or Plateau Honing Brush or Truing Grit

CONTAINS: <96% Aluminum Oxide CAS 1344-28-1, <99% Silicon Carbide CAS 409-21-2, <45% Sulfur CAS 7704-34-9, <30% Phenol-formaldehyde polymer (cured) CAS 9003-35-4, <15% Chemical Frits (Lead Free) CAS 65997-18-4, <9% Quartz CAS 14808-60-7, <6% Titanium dioxide CAS 13463-67-7, <5% Silica, cristobalite CAS 14464-46-1, <2% Chromium (III) oxide CAS 1308-38-9, <2% Urea formaldehyde polymer (cured) CAS 98011-05-6 and <2% Aluminum CAS 7429-90-5

DANGER

Causes skin irritation. Causes serious eye irritation. May cause cancer. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Appearance: Various Physical State: Solid Odor: None

FIRST AID

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation persists.

IF ON SKIN: Wash skin with soap and water. Get medical attention if irritation persists.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell.

IN CASE OF FIRE

Use water spray, dry chemical powder, carbon dioxide or alcohol resistant foam to extinguish. Do not breath fumes.



As a solid object the honing stone presents no hazard at normal temperatures. However when used in the normal manner or if modified for use by abrading, grinding, cutting or processing in another fashion that creates potentially hazardous dust or fumes can result in exposure by inhalation, swallowing or come in contact with skin or eyes. The information below is for these instances.

PRECAUTIONARY STATEMENTS

PREVENTION: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Wear protective gloves /protective clothing/ eye protection/ face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. **GENERAL ADVICE:** If exposed or concerned: Get medical attention/advice. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. **SKIN: IF ON SKIN:** Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. **INHALATION: IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. **STORAGE:** Store locked up. Store in a well-ventilated place. Keep container tightly closed. **DISPOSAL:** Dispose of contents/container to an approved waste disposal plant. **HAZARD NOT OTHERWISE CLASSIFIED (HNOC):** Not applicable. **OTHER INFORMATION:** Harmful to aquatic life with long lasting effects.

SUNNEN PRODUCTS
7910 MANCHESTER RD. ST.
LOUIS, MO 63143 U.S.A.
314-781-2105

LAB-084-US(en)-ABR CONV VIT RESIN SUPER VIT PHT DB